

Doyon Convection Ovens JA Series



JA14



JA12SL



Superior Air Flow

JA Series

Specifications

Model	Crated Weight	Overall Dimensions			Interior Dimensions			Pan Capacity (18"x26")	Shelf Spacing	Gas System			Water Inlet	Electrical System *Ground wire not included.					
		W	D	H	W	D	H			BTU	D.H.	G.I.		Volts	Phases	Amps	kW	Wires*	Hz
JA4	425 (193)	32 1/2" (826)	40" (1016)	31" (787)	27 1/2" (699)	20" (508)	17 1/2" (445)	4	3 1/2" (89)	-	-	-	1/4" (6)	120/208 120/240	1 / 3 1 / 3	39 / 22 34 / 20	8 8	2 / 3 2 / 3	60
JA4SC	650 (295)	32 1/2" (826)	37" (940)	71" (1803)	27 1/2" (699)	20" (508)	17 1/2" (445)	4	3 1/2" (89)	-	-	-	1/4" (6)	120/208 120/240	1 / 3 1 / 3	39 / 22 34 / 20	8 8	2 / 3 2 / 3	60
JA6	700 (318)	36 1/2" (927)	48 1/4" (1226)	34 3/4" (883)	25 1/2" (648)	30 1/2" (775)	26 1/4" (667)	6	3 1/2" (89)	-	-	-	1/4" (6)	208 240	1 / 3 1 / 3	52 / 33 45 / 28	10.8 10.8	2 / 3 2 / 3	60
JA6G*	760 (345)	36 1/2" (927)	52 3/4" (1340)	34 3/4" (883)	25 1/2" (648)	29 1/2" (749)	26 1/4" (667)	6	3 1/2" (89)	65 000	4" (102)	1/2" (13)	1/4" (6)	120	1	6.5	0.8	2	60
JA6SL	700 (318)	38 3/8" (975)	37 5/8" (956)	34 5/8" (879)	26 3/4" (679)	19 1/2" (495)	26 1/4" (667)	6	3 1/2" (89)	-	-	-	1/4" (6)	208 240	1 / 3 1 / 3	52 / 33 45 / 28	10.8 10.8	2 / 3 2 / 3	60
JA8	840 (381)	36 3/8" (924)	52" (1321)	41 5/8" (1057)	23 1/2" (597)	31" (787)	33 1/2" (851)	8	3 1/2" (89)	-	-	-	1/4" (6)	208 240	1 / 3 1 / 3	51 / 33 45 / 28	10.8 10.8	2 / 3 2 / 3	60
JA8G*	900 (409)	36 3/8" (924)	54 1/2" (1384)	41 5/8" (1057)	23 1/2" (597)	30" (762)	33 1/2" (851)	8	3 1/2" (89)	65 000	6" (152)	1/2" (13)	1/4" (6)	120	1	4.7	1.2	2	60
JA12SL	1060 (481)	38 3/8" (975)	37 5/8" (956)	73" (1854)	26 3/4" (679)	19 1/2" (495)	26 1/4" (667)	12	3 1/2" (89)	-	-	-	1/4" (6)	208 240	1 / 3 1 / 3	103 / 66 90 / 52	21.5 21.5	2 / 3 2 / 3	60
JA14	1135 (515)	38 1/2" (978)	49 1/4" (1251)	73" (1854)	25 1/2" (648)	30 1/2" (775)	28" (711)	14	3 1/4" (83)	-	-	-	1/4" (6)	208 240	1 / 3 1 / 3	103 / 66 90 / 58	21.5 21.5	2 / 3 2 / 3	60
JA14G	1300 (590)	38 1/2" (978)	53 5/8" (1362)	73" (1854)	25 1/2" (648)	29 1/2" (749)	28" (711)	14	3 1/4" (83)	130 000	6" (152)	1/2" (13)	1/4" (6)	208 240	1 1	9 7	2 2	2 2	60

* Draft Hood G.I. Gas Inlet (NPT) W.I.: Water Inlet (NPT) CODING Prefix JA: Jet Air Suffix G: Gas SL: Side pan loading
JA6G & JA8G: NEMA 5-15P Plug

www.doyon.qc.ca • www.nu-vu.com